

## Spiegel Southern Yellow Pine

- Species:** Southern Yellow Pine
- Source:** Spiegel Catalog Warehouse, Chicago
- Grade:** Heritage Original™
- Knots:** Unlimited. Most knots are sound, some are broken, loose or open. Open or broken knots up to ¾" are allowed.
- Checks/Cracks:** Unlimited as long as board is sound. End cracks to extend no more than 6" into board.
- Nail/Bolt Holes:** Regular small (1/4" to 3/8") nail holes. No bolt holes.
- Grain Pattern:** Mixed. Gray and blue-gray staining is common. Heartwood & Sapwood mixed.
- Percentage Sapwood:** Unlimited.
- Color:** Sapwood is blonde to yellow. Heartwood is a rich reddish brown.
- Weight:** 2.4 lb./Sq. Ft.
- Characteristics:**
- Standard Dimensions:**
- a. Thickness: ¾"
  - b. Width: 4¾"
  - c. Length: 18" – 10' with no more than 15% of total footage shorter than 4'.
- Textures Available:** Smooth, Wire Brushed, Circular Sawn, Skip Sawn, 3D, Hand Scraped, Hand Scraped Plus, Draw Knife Distressed.
- Additional Options:** Machine, Hand Scraped or Draw Knife Beveled Edges & Ends, Pegs.
- Installation:** **Texturewood®** flooring can be installed on and above grade level. It is not recommended that this flooring be installed below grade. Installation procedures may vary (i.e. reclaimed versus new floors, or strip versus plank flooring, etc.) We recommend consulting with a professional flooring installer, and following National Wood Flooring Association installation guidelines.
- Moisture Content:** Shipped at 6%-8.5% average. Moisture content may vary some based on the humidity level of the installation site. Therefore, we recommend flooring be acclimated on the job site in the same environment in which it will remain once installed, for a period of 1 to 3 weeks.
- Finishes:** Consult with your professional flooring installer.
- Stability:** Will expand and contract less than Red Oak.
- Waste:** We recommend approximately 15% cut and waste on traditional sub floor installations.
- Janka Rating:** 870
- Samples:** Character marks such as knots, checks/cracks, sap, and natural color and grain patterns will vary with each plank. This is even more so in reclaimed wood due to weathering and use. Your floor will vary somewhat from samples and pictures shown.

**Texturewood®** flooring products are processed from solid kiln-dried stock lumber. These flooring materials should be acclimatized and installed in accordance with the National Wood Flooring Association recommendations. As each installation is unique, we urge you to contact a professional flooring installer for recommendations concerning jobsite evaluation and installation. Please contact your **Texturewood®** representative with any questions, or view our website for general tips and guidelines on installation.

PO Box 93 • 1446 E 1500 N  
Terreton, ID 83450 US  
(208) 663-4329 • Fax: (208) 663-4729  
Email: [sales@texturewood.com](mailto:sales@texturewood.com)  
[www.texturewood.com](http://www.texturewood.com)